

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: UCA150 Clearcoat-Aerosol

Manufacturer: Color Rite Distributing Inc.
1817 E. Ave. Q, Ste. C-24
Palmdale, CA 93550

Information Phone Number: 800-736-7980

Emergency Phone Number:

MSDS Date of Preparation: 01/08/2009

Product Use: Paint for consumer and professional use

SECTION 2: HAZARDS IDENTIFICATION

Liquid with a solvent odor in an aerosol container.

EMERGENCY OVERVIEW: DANGER! Extremely flammable aerosol. Contents under Pressure. Heated can may rupture. Keep away from heat, sparks, flames and other sources of ignition. Do not smoke. Turn off stoves, heaters, electric motors and other sources of ignition until all vapors/odors are gone. Causes eye irritation. May cause skin irritation. May be harmful if absorbed through the skin. Inhalation of vapors may cause irritation, headache, dizziness and drowsiness. Harmful or fatal if swallowed. Contains toluene which may harm the unborn child.

This product is hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). Category: Flammable, Compressed Gas, Irritant, Target Organ Effects.

Refer to Section 11 for detailed information on health effects.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	%
Propane	74-98-6	14
Butane`	106-97-8	13
Toluene	108-88-3	17
Medium Aliphatic Hydrocarbons	64742-94-5	3
Acetone	67-64-1	41
Ethyl 3-Ethoxypropionate	763-69-9	4

SECTION 4: FIRST AID MEASURES

Eye: Rinse thoroughly with water for at least 15 minutes, holding the eye lids open to be sure the material is washed out. Get immediate medical attention.

Skin: Remove contaminated clothing. Wash exposed area with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

Inhalation: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Ingestion: Ingestion is an unlikely route of exposure for aerosol products. If ingestion occurs rinse mouth with a small amount of water. Immediately call local poison control center or go to an emergency department. Aspiration hazard – DO NOT Induce Vomiting. Never give anything by mouth to an unconscious or drowsy person.

MATERIAL SAFETY DATA SHEET

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media: Use foam, carbon dioxide or dry chemical.

Special Fire Fighting Procedures: Wear approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

Unusual Fire Hazards: Extremely flammable aerosol. Contents under Pressure. Prolonged exposure to temperatures above 120°F(48.9°C) may cause cans to burst. Keep this product away from heat, open flames, sparks or other sources of ignition (i.e. pilot lights, electric motors, static electricity). Invisible vapors can travel along surfaces to a source of ignition and flash back. Do not smoke while using this product or until all vapors have dissipated. Container may rupture or explode in the heat of a fire. Do not apply to hot surfaces. Vapors may form explosive mixtures with air and will collect in low areas.

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, hydrocarbons.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill: Evacuate the area. Wear appropriate personal protective equipment. Eliminate all sources of ignition. Ventilate area. Collect material into a suitable, clean container for disposal. Report spills and releases as required to appropriate authorities.

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contact with eyes and skin. Avoid breathing vapors and mists. Use only with adequate ventilation. Wash exposed skin thoroughly with soap and water after use. Keep away from heat, sparks, flames and all other sources of ignition (i.e. pilot lights, electric motors, static electricity). Do not smoke while using this product or until all vapors have dissipated. Do not puncture or incinerate container.

Storage Store in a cool, well ventilated area at temperatures below 120°F (48.9°C). Do not store in direct sunlight. Store large quantities in buildings designed and protected for storage flammable aerosols.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
Propane	1000 ppm TWA OSHA PEL 1000 ppm TWA ACGIH TLV (as aliphatic hydrocarbon gas)
Butane	1000 ppm TWA ACGIH TLV (as aliphatic hydrocarbon gas)
Toluene	200 ppm TWA, 300 ppm Ceiling OSHA PEL 50 ppm TWA skin ACGIH TLV
Medium Aliphatic Hydrocarbons	None Established
Acetone	1000 ppm TWA OSHA PEL 500 ppm TWA, 750 ppm STEL ACGIH TLV
Ethyl 3-Ethoxypropionate	None Established

Ventilation: Use only with adequate ventilation. For operations where the occupational exposure limit may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits. Use explosion-proof equipment where required.

Respiratory Protection: For operations where the occupational exposure limit may be exceeded, a NIOSH approved

MATERIAL SAFETY DATA SHEET

Chronic Hazards: Prolonged or repeated inhalation of the solvents in this material may result in liver, kidney and permanent brain and nervous system damage. Intentional misuse of this product by concentrating and inhaling vapors may be fatal. Toluene has been found to cause adverse fetal effects in laboratory animals and in humans intentionally inhaling toluene.

Carcinogen Status: None of the components of this product are listed as a carcinogen by IARC, NTP or OSHA.

Medical Conditions Aggravated by Exposure: Persons with pre-existing skin, nervous system, liver, kidney, respiratory and cardiovascular disorders may be at increased risk of exposure.

Acute Toxicity Data:

Toluene: LD50 oral rat 5 g/kg, LD50 skin 12.12 g/kg, LC50 inhalation rat 4000 ppm/4 hr

Acetone: LD50 oral 5.8 g/kg

Ethyl 3-Ethoxypropionate: LD50 oral 5 g/kg

SECTION 12: ECOLOGICAL INFORMATION

No data available at this time.

SECTION 13: DISPOSAL CONSIDERATIONS
--

Waste from this product may be classified as hazardous waste. Dispose in accordance with all local, state and federal regulations. Do not incinerate. Depressurize container.

SECTION 14: TRANSPORT INFORMATION
--

DOT Shipping Description: Aerosols, 2, UN1950

SECTION 15: REGULATORY INFORMATION

Federal Regulations

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). Category: Flammable, Irritant, Target Organ Effects

CERCLA 103 Reportable Quantity: Releases of this product in excess of the reportable quantity of 5880 lbs (based on toluene – 1000 lb RQ) are reportable to the National Response Center. Many states have more stringent reporting requirements. Report spills and other releases as required under federal, state and local regulations.

SARA TITLE III:

Hazard Category for Section 311/312: Acute Health, Chronic Health, Fire Hazard

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements:

Toluene	108-88-3	17
---------	----------	----

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

STATE REGULATIONS:

MATERIAL SAFETY DATA SHEET

California Proposition 65: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm:

INTERNATIONAL REGULATIONS

Canadian WHMIS Classification: Class B5 Flammable Aerosol, Class D-2-A (Very Toxic Material causing other toxic effects).

This product has been classified in accordance with the hazard criteria in the CPR and the MSDS contains all the information required by the CPR.

Canadian CEPA Status: All of the components of this product are listed on the Canadian DSL.

NFPA RATING:	Health = 2	Fire = 4	Reactivity = 0
HMIS RATING:	Health = 2*	Fire = 4	Reactivity = 0

While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.